Cat® Prime Application Grease

For medium-load, medium-speed applications

NLGI Grade 2



Discover the Difference

Factory-Fill—Used as standard factory-fill for most Cat machines.

Long Life—Lithium complex grease, enhanced with 3% molybdenum disulfide (moly), in medium-load, medium-speed and moderate temperature applications in a low moisture environments.

Reduced Component Wear—Resists softening and protects parts from wear.

Corrosion Protection—Resists oxidation and protects metal against rust. Will not corrode or damage steel, copper bearing alloys or conventional seal material.





Cat® Prime Application Grease

Grease Selection Guide

Cat Extreme Application Grease 1 NLGI 1 (-20 to 140°C / -4 to 284°F)

Cat Extreme Application Grease - Desert NLGI 2 (-10° to 140°C / +14° to 284°F)

With 5% Moly

Cat Prime Application Grease NLGI 2 (-20 to 140°C / -4 to 284°F)

Cat Ball Bearing Grease NLGI 2 (-20° to 160°C / -4° to 320°F)

Without Molv



Cat Extreme Application Grease - Arctic **NLGI 0.5** -50° to 130°C / -58° to 266°F) With 5% Molv

Without Molv

Low Load & Low Speed

Cat Utility Grease

NLGI 2

(-20 to 140°C / -4 to 284°F)

Low Load & **High Speed**

Working **Environment**

High Load & **High Speed** * All temperatures are Operating Temperatures

High Temp

Low Temp

Med Load & Med Speed

Typical Properties	
NLGI	2
Color	Gray Black
Molybdenum Disulfide, %	3
Operating Temperature Range, °C	-20 to +140
Operating Temperature Range, °F	-4 to +284
Base Oil Type	Mineral
ASTM D445 Base Oil Viscosity 40°C, mm²/s	320
Thickener Type	Lithium Complex
ASTM D2265 Dropping point, °C	260
ASTM D217 Penetration, worked 60, mm/10	280
ASTM D1831 Roll stability, penetration change, mm/10	-3
ASTM D2266 4 Ball wear, scar diameter, mm	0.47
ASTM D2596 4 Ball weld load, kg	400
ASTM D1743 Rust prevention	Pass
ASTM D4048 Copper corrosion	1A
ASTM D1264 Water wash-out, 79°C, mass %	6

Recommended Use

Cat Prime Application Grease is recommended for grease fittings and lubrication points in medium-load, medium-speed applications where operating temperatures range from -20°C to +140 °C (-4°F to +284 °F).

Health and Safety

For information on proper use for health, safety and environment, please refer to the Material Safety Data Sheet (MSDS). Read and understand the MSDS before using this product. Always observe good hygiene measures. For a copy of the MSDS, contact us or visit the web at www.catmsds.com.

The values shown are typical values and should not be used as quality control parameters to either accept or reject product. Specifications are subject to change without notice

CAT DEALERS DEFINE WORLD-CLASS PRODUCT SUPPORT.

We offer you the right parts and service solutions, when and where you need them.

The Cat Dealer network of highly trained experts keeps your fleet up and running to maximize your equipment investment.

BUILT FOR IT.

PEHJ0404 www.cat.com